

RTD BULK WIRE

Reotemp RTD wire is supplied for extending RTD signal leads. Wire options include teflon insulation with stranded wire for temperatures up to 400°F, or fiberglass insulation with stranded wire for temperatures up to 900°F. Stainless steel overbraid is a configurable option for extra protection.



RTD

HOW TO ORDER: Choose options to build a part number. For example: **RTD24T2-3-500**

RTD24	T2		3		-500																		
WIRE GAUGE	INSULATION TYPE	DRAIN WIRE (OPTIONAL)	NUMBER OF CONDUCTORS/ WIRES	WIRE OVERBRAID (OPTIONAL)	LENGTH IN FEET																		
<p>RTD24 = 24 AWG RTD Extension, Wire Nickel Plated (Standard)</p> <p>RTD20 = 20 AWG RTD Extension Wire Nickel Plated</p>	<table border="1"> <tr> <td>T2</td> <td>Teflon Stranded Wire</td> <td>Up to 400°F</td> </tr> <tr> <td>F2</td> <td>Fiberglass Stranded Wire</td> <td>Up to 900°F</td> </tr> </table>	T2	Teflon Stranded Wire	Up to 400°F	F2	Fiberglass Stranded Wire	Up to 900°F	<p>D = Drain Wire with Mylar Shield</p>	<table border="1"> <tr> <td>3</td> <td>3 Wire</td> <td>Red, Red, White</td> </tr> <tr> <td>4</td> <td>4 Wire</td> <td>Red, Red, White, White</td> </tr> <tr> <td>6</td> <td>6 Wire</td> <td>Red, Red, White, Black, Black, Yellow</td> </tr> <tr> <td>8</td> <td>8 Wire</td> <td>Red, Red, White, White, Black, Black, Yellow, Yellow</td> </tr> </table>	3	3 Wire	Red, Red, White	4	4 Wire	Red, Red, White, White	6	6 Wire	Red, Red, White, Black, Black, Yellow	8	8 Wire	Red, Red, White, White, Black, Black, Yellow, Yellow	<p>SSO = Stainless Steel Overbraid</p>	<p>-10 = 10 feet</p> <p>-50 = 50 feet</p> <p>-100 = 100 feet</p> <p>-500 = 500 feet</p> <p>-1000 = 1000 feet</p>
T2	Teflon Stranded Wire	Up to 400°F																					
F2	Fiberglass Stranded Wire	Up to 900°F																					
3	3 Wire	Red, Red, White																					
4	4 Wire	Red, Red, White, White																					
6	6 Wire	Red, Red, White, Black, Black, Yellow																					
8	8 Wire	Red, Red, White, White, Black, Black, Yellow, Yellow																					