

REOCLICK™ SANITARY RTD

Reotemp's patented ReoClick™ makes disconnecting and reconnecting your temperature sensor a snap, literally. With the click of a button, your temperature sensor is released from the female tri-clamp allowing it to be quickly placed into a temperature bath for a calibration check and then securely snapped back into place, in a matter of seconds. The ReoClick replaceable element design also allows the sensor to be easily replaced with minimal downtime.



Made in USA



Patented
US Patent
D769137




FEATURES / BENEFITS


- 3-A Approved Wetted Surfaces (32 Ra max.) with 3-A Certificate Provided
- Connect/disconnect Sensor with a Click of a Button for Easy Calibration
- Fully Sealed for Washdown (IP67)
- Sealed Spring Loaded Sensor can be Placed Directly into Calibration Bath
- Callendar-Van Dusen Coefficients Available for Optimized Sensor Accuracy (Hi-Accuracy™ Curve Plot Option)

SPECIFICATIONS

Accuracy	Class A = $\pm (0.15 + 0.002 t)^{\circ}\text{C}$ [-30/200°C] 1/10 B = $\pm (0.03 + 0.0005 t)^{\circ}\text{C}$ [0/50°C] Outside of State Ranges = $\pm (0.3 + 0.005 t)^{\circ}\text{C}$ [-200/200°C]
RTD	100 ohm Pt., 0.00385 $\Omega/\Omega^{\circ}\text{C}$, 3-wire or 4-wire
Temperature Range	-328°F/400°F
Process Connection	Tri-Clamp: 1.5", 2", 2.5", 3", 4" or 3/4"
Wetted Finish	Ra 32 Max. / Ra 20 Max. (Optional), Electropolish (Optional)
Stem Length	2" to 36" std lengths; custom lengths available.
Straight Stem Diameters	1/4", 3/8", 3/16"
Reduced Stem Diameters	3/8" reduced to 3/16" tip, 1/2" reduced to 1/4" tip
Wire Type	Teflon insulated 24 AWG stranded, PVC insulated 24 AWG Stranded, or Teflon insulated 24 AWG Stranded with Aluminum Mylar Shield and Drain Wire



M12 Output



Wire Output

REOCLICK™ SANITARY RTD

BUILD YOUR REOCLICK: Choose options to build a part number. For example: RSRAS3D025T75MP-TS

MODEL	RTD ACCURACY	ELEMENT	STEM DIAMETER	STEM LENGTH	PROCESS CONNECTION "C"
RSR REOCLICK Sanitary RTD	A Class A, 100Ω, 385 Curve(Standard) T = 1/10 B, 100Ω, 385 Curve	S3 Single Element S3 = Single 3-Wire S4 = Single 4-Wire	D Straight Stems A = 1/4" Diameter D = 3/16" Diameter (Standard) F = 3/8" Diameter	025 2.5" Stem 030 = 3" Stem 040 = 4" Stem 060 = 6" Stem 090 = 9" Stem 120 = 12" Stem 180 = 18" Stem 240 = 24" Stem 360 = 36" Stem ??? = Length in inches up to 72"	T75 1.5" Tri-Clamp T15 = 1.5" Tri-Clamp T20 = 2" Tri-Clamp T25 = 2.5" Tri-Clamp T30 = 3" Tri-Clamp T40 = 4" Tri-Clamp T75 = 3/4" Tri-Clamp
MP Wire Cable MP = M12 Plug MF = M12 with Female Connector Only MW = M12 with Female Connector and Wire	WIRE LENGTH (OPTIONAL) Specify only when WC or MW outputs are chosen. ??? = Wire Length in Inches, Example: 072 = 72".	WIRE TYPE (OPTIONAL) Specify only when WC or MW outputs are chosen. T = Teflon Insulated (Standard for WC Output) P = PVC Insulated (Standard for MW Output) A = Teflon w/ Aluminum Mylar Shield and Drain	WIRE TERMINATION (OPTIONAL) Specify only when WC or MW outputs are chosen. S = Stripped (Standard) L = Spade Lugs T = Terminal Pins M = Copper Crimps	OPTIONS -TS = Stainless Steel Tag -RA = Ra 20 Max Wetted Finish with Certificate -R3 = Calibration Certification, 3 Points (32°F, 100°F, 190°F) -R1 = Calibration Certification, 1 Point (100°F) -C3 = Calibration Certification, 3 Points (Customer Picks) -C1 = Calibration Certification, 1 Point (Customer Picks) For additional options see page 147.	

SANITARY

Tri-Clamp Size	Diameter "C"	
	in	mm
3/4"	0.984	25
*1.5"	1.984	50.4
2"	2.516	63.9
2.5"	3.047	77.4
3"	3.579	90.9
4"	4.682	118.9

*1.5" tri-clamp fits 1.5" and 1" tri-clamp fittings

THERMOCOUPLE & RTD OPTIONS

		Thermocouple	RTD	Digital Thermometers	Handheld Digital
CERTIFICATION OPTIONS					
-R1	1 Point Calibration Certification, Reotemp Chooses	✓	✓	✓	✓
-R3	3 Point Calibration Certification, Reotemp Chooses	✓	✓	✓	✓
-C1	1 Point Calibration Certification, Customer Chooses	✓	✓	✓	✓
-C3	3 Point Calibration Certification, Customer Chooses	✓	✓	✓	✓
-CC	Certificate of Conformance	✓	✓	✓	✓
-CS	NIST Calibration Sticker (No Logged Points)	✓	✓	✓	✓
OTHER OPTIONS					
-VB	Hi-Vibration	N/A	✓	✓	✓
-AC	Hi-Accuracy	N/A	✓	N/A	N/A
-PS	Pointed Stem	✓	✓	✓	✓
-TF	Teflon Coating	✓	✓	✓	✓
-SS	316 SS stem	N/A	STD	✓	✓
-NL	No Logo	✓	✓	✓	✓
-HT	Heat Transfer Compound (2 oz)	✓	✓	✓	N/A
-GL	Plain Glass Lens	N/A	N/A	✓	✓
-CL	Custom Logo Dial	N/A	N/A	✓	✓
-BP	Replacement Battery Pack	N/A	N/A	✓	✓
-WD	White Dial	N/A	N/A	✓	✓
-AS	Allows to Fit 1-1/4-18 Industrial Thermowell	✓	✓	✓	N/A
TAG OPTION					
-TS	Stainless Steel Tag (1-10 Characters)			✓	
-TM	Stainless Steel Tag (11-80 Characters)			✓	
-TP	Paper Tag			✓	

✓	Indicates that the option is available with this model.
N/A	Indicates the option is not available with this model.
STD	Indicates standard options with no additional cost.