

DIAPHRAGM SEAL ACCESSORIES

DRY CAPILLARY



- Used When Pressure Instrument Needs to be Removed from Direct Contact of Installation Point
- All-welded 316SS Construction
- Available up to 100 ft. in Length (Max 40 ft. in diaphragm seal assembly)
- Max Working Pressure of 10,000 psig
- 2mm ID Standard
- Note: if capillary is part of a filled diaphragm seal system use 3 digit mounting code per page 57 (Example: "A25" = 25' of armored capillary, threaded to seal)

HOW TO ORDER: Choose options to build a part number. For example: **DXC4M4M10A-TS**

| MODEL | INSTRUMENT CONNECTION | PROCESS CONNECTION | LENGTH IN FEET | PROTECTION | OPTIONS |
|------------------------|--|--|--|--|--|
| DXC | 4M | 4M | 10 | A | -TS |
| DXC = Capillary | 4M = 1/4" Male NPT 4F = 1/4" Female NPT 2M = 1/2" Male NPT 2F = 1/2" Female NPT | 4M = 1/4" Male NPT 4F = 1/4" Female NPT 2M = 1/2" Male NPT 2F = 1/2" Female NPT | 05 = 5 ft. 10 = 10 ft. 20 = 20 ft. ?? = Specify, Length in feet | A = Stainless Steel Armor P = PVC Coated Stainless Steel Armor B = Bare Capillary Tubing (Rare) | -3M = 3mm ID (10 ft. Max) -TS = Stainless Steel Tag (1-10 Characters) |

FLUSH RINGS



- Used to Flush Process Fluid or Provide Access for Field Calibrations
- Machined from Solid Bar Stock
- Pressure Ratings Up to ANSI Class 2500
- For Use with W9FF and W9FR Diaphragm Seals (Raised Face)

HOW TO ORDER: Choose options to build a part number. For example: **DXFR322S-PM**

| MODEL | PIPE SIZE | PORT SIZE | NUMBER OF PORTS | MATERIAL | OPTIONS |
|--------------------------|--|--|---|--|--|
| DXFR | 3 | 2 | 2 | S | -PM |
| DXFR = Flush Ring | H = 1-1/2" ANSI 2 = 2" ANSI 3 = 3" ANSI 4 = 4" ANSI | 4 = 1/4" NPT 2 = 1/2" NPT | 1 = One Port 2 = Two Ports (180° Opposed) 4 = Four Ports (90° Apart) | S = 316SS H = Hast-C276 M = Monel J = Titanium 2 = Duplex 2205 D = Alloy 20 | -MR = Mill Certification -PM = Positive Material Identification Certification -GS = 1/4" NPT SS Plug -JS = 1/2" NPT SS Plug |

DIAPHRAGM SEALS