

TEST PLUGS AND ACCESSORIES

Reotemp's Test Plugs are designed for users to quickly take pressure or temperature readings without shutting down the line or needing permanently installed pressure gauges. Gauges, thermometers, and accessories are also offered to meet any applicational needs.



PTB Plug

FEATURES / BENEFITS

- Self-Sealing Nordel or Neoprene Core
- Ideal for Quick Pressure or Temperature Checks
- Brass, Lead-Free Brass, and Stainless Steel Constructions Available

SPECIFICATIONS

Body/Cap Materials	Brass (Standard) Lead-Free Brass, Stainless Steel
Connection Sizes	1/4" and 1/2" (Standard) 1/8" and 3/8"
Process Limits	Nordel: 350°F (Standard) Neoprene: 200°F
Retainer	Included (Plastic Material)

HOW TO ORDER: Choose options to build a part number. Ex: PTBND-4

PTB

ND

-4

BODY & CAP

CORE

CONNECTION

PTB = Brass
PTL = Lead-Free Brass
PTS = Stainless Steel

ND = Nordel
NP = Neoprene

4 = 1/4" Male NPT
2 = 1/2" Male NPT
8 = 1/8" Male NPT
5 = 3/8" Male NPT

Extensions



PTBEX

3

-4

BODY MATERIAL

LENGTH

CONNECTION

PTBEX = Brass
PTLEX = Lead-Free Brass

(Blank) = Standard 1.75"
3 = 2.75"
5 = 4.75"

4 = 1/4" Male NPT
2 = 1/2" Male NPT
8 = 1/8" Male NPT
5 = 3/8" Male NPT

Gauge Adaptors



PTBGA

-4

-8

BODY MATERIAL

CONNECTION

PROBE

PTBGA = Brass Gauge Adaptor

-4 = 1/4" Female NPT

8 = 1/8" OD SS Probe
16 = 1/16" OD SS Probe